



Industrial waterproof telephone

EX-BT27

Becke EX-BT27 is a rugged industrial telephone built for harsh environments. Suitable for underground pipe galleries, subway expressway tunnels, metal mines, various power plants, steel mills, ship docks, oil fields, outdoor jungles, large production workshops, etc. in harsh environmental places such as those requiring waterproofing, moisture-proofing, fire prevention, noise reduction, etc. IP66 protection level, waterproof, moisture-proof, dust-proof, anti-freezing;

Highlights

- ✓ Can directly connect to Ethernet, across subnets and routers
- ✓ Number pad dialing, call any terminal, achieve full-duplex intercom (default)
- ✓ System supports SIP 2.0 protocol
- ✓ Broadcast announcements to authorized areas
- ✓ Professional protective design for the phone case, waterproof, dustproof, no need for waterproof cover, beautiful and practical
- ✓ International standard integrated circuits are used inside the phone, featuring clear calls and stable operation
- ✓ Supports POE power supply, with surge protection and anti-interference capabilities
- ✓ FRP shell, stainless steel keypad, explosion-proof noise-reducing receiver, zinc alloy hook
- ✓ 30W high-quality power amplifier for amplification, clear and loud sound quality
- ✓ Automatic answering function, can realize paging broadcast
- ✓ Setting of hotline numbers, answering machine can achieve automatic dialing
- ✓ External 25W amplifying speaker, receiver and volume can be adjusted through the keyboard
- ✓ Exterior surface is hot-pressed anti-static coating, good anti-static performance, corrosion-resistant
- ✓ Key components such as handles, hooks, and keyboards are self-developed and produced, with strict quality control and prompt after-sales response.

Detailed parameters

Explosion proof signs	IK10
Rated voltage	AC220V
Network communication protocol	TCP、UDP、ICMP、SIP2.0
Frequency response	250~3000 Hz
Amplification output power	10~25W
Protection level	IP66
Ambient temperature	-40~+60°C
Atmospheric pressure	80~110KPa
Relative humidity	≤95%
Lead out wire hole	3-G3/4"
Installation method	Wall mounted
Material	FRP (Fiber Reinforced Plastic)
Color	Yellow
External size	343×294×206 mm
Overall weight of product	12kg